

## CARA Design fireplaces with lifting door

**Design accumulation fireplaces Romotop CARA response to the trends and needs of modern interior architecture. Finely balanced proportions, clean lines and dominant three-side glazing creates an impressive complex satisfying even the most demanding customers.**

The CARA CS 02 and CARA CS N 03 fireplaces are also suitable for low energy houses. They have sliding doors with precise and easy operation SILENT LIFT. The combustion chamber is clad with fireclay fittings. Standard combustion chamber model is without grate, but it can be easily modified to a model with grate. In order to optimise the combustion process, tertiary air is led to the upper section of the combustion chamber. Innovative exhaust gas management system DOUBLE SPIN increases overall efficiency of the fireplace. As standard, the exhaust gas is discharged via a smoke outlet in the top or in the back of the unit. Secondary air supply onto the inner side of the door is an efficient solution to avoid dirt deposits, hence, you will not be distracted from viewing into the flames. Primary and secondary air intake is easily controlled by one control element. Sufficient air for an optimum combustion process will be provided by the EAI system (external air intake from the exterior). The fireplace can be improved by installation of accumulation fittings, intended for accumulation of heat and its subsequent radiation back into the room continuing up to several hours after the flame has extinguished. CARA fireplaces are clad with large natural stone plates or surface finish metal. Thanks to back side shielding, the fireplace can be installed close to the wall.

### CARA CS 02

serpentine



Prices on request at your seller

Split glazing - order code: **CARA CS 02**



## Technical parameters

Height	1648 mm
Width	774 mm
Depth	577 mm
Door height	420 mm
Door width	520 mm
Door depth	271 mm
Weight	316 kg
Regulated output	2,9-7,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1346 mm
Draught	12 Pa
Efficiency	82,1 %
Average wood consumption	1,6 kg/h
A+	

## Accessories

Accumulation set for design fireplaces (AKKUM CARA 02)  
AIRBOX 01  
CARA CS GLASS PLINTH  
GRATE SET for Romotop CARA design fireplace stove

## Download

Declaration about qualities  
EC declaration of conformity  
Ecodesign (EU 2015/1185)  
Energy label and product sheet  
Energy label (EU 2015/1186)  
General instructions  
Installation instructions  
Technical documentation  
Technical sheet  
Warranty sheet  
Download our catalogue!