

## **SPIRIT Tiled accumulation fireplaces with lifting door**

**Appealing fireplace with three-side glazing, sophisticated details and focus on overall design and technical workmanship: These elements feature an impressive complex, addressing even the most demanding customers. The structure of the fireplace is covered with large format ceramic tiles that are ideal for efficient heat transmission.**

Tiled accumulation fireplaces SPIRIT C1 are also suitable for low energy houses. They have sliding doors with precise and easy operation SILENT LIFT. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. In order to optimise the combustion process, tertiary air is led to the upper section of the combustion chamber. Innovative exhaust gas management system DOUBLE SPIN increases overall efficiency of the unit. Standard flue gas outlet is on the top or in the back. Secondary air intake will provide for door glass cleaning to avoid dirt deposits, a person sitting at the stove can look into the fire, without being disturbed by dirty glass of the door. Primary and secondary air intake is easily controlled by a one control element. Sufficient air for an optimum combustion process will be provided by the EAI system (external air intake from the exterior). The fireplace can be improved by installation of accumulation fittings, intended for accumulation of heat and its subsequent transfer back into the room, continuing even during several hours after the flame has extinguished. Thanks to back side shielding, the stove can be installed close to the wall. SPIRIT C2 M model is fitted with removable metal cornice.

### **SPIRIT C2 M**

tile



Prices on request at your seller

order code: **SPI C2 M**



## Glaze colours



## Technical parameters

Height	1703 mm
Width	870 mm
Depth	550 mm
Weight	319 kg
Regulated output	3,9-10,1 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1320/1370 mm
Draught	12 Pa
Efficiency	82,8 %
Average wood consumption	2,2 kg/h
A+	

## Accessories

Accumulation set for design fireplaces (AKKUM CARA 01)  
CARA C GLASS PLINTH

## Download

[Declaration about qualities](#)  
[EC declaration of conformity](#)  
[Ecodesign \(EU 2015/1185\)](#)  
[Energy label and product sheet](#)  
[Energy label \(EU 2015/1186\)](#)  
[General instructions](#)  
[Installation instructions](#)  
[Technical documentation](#)  
[Technical sheet](#)  
[Warranty sheet](#)  
[Download our catalogue!](#)