

HEAT fireplace inserts TUNNEL

Connecting two areas was never so simple and elegant thanks to the HEAT tunnel fireplace inserts. Enjoy living flames that create a perfect atmosphere in different parts of your home.

HEAT fireplace inserts have large-format printed glazing that allows you to experience the fire in a unique way. Thanks to their tunnel design, wood can be added from both sides. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with chamotte bricks (HT3Z 01) or heat-resistant bricks named IGNITON (HT3LF 04) and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

HEAT T 3g 70.50.01



Prices on request at your seller

order code: **HT3Z 01**

with side opening

designed for convection and accumulation operation

maximum of 2 side accumulation sets



DOUBLE
SPIN



Technical parameters

Height	1192 mm
Width	808 mm
Depth	570 mm
Door height	467 mm
Door width	664 mm
Weight	190 kg
Regulated output	4,0-10,3 kW
Smoke flue diameter	150-180 mm
Flue socket diameter	180 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	82,3 %
Average wood consumption	2,2 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

FRAME H3Z RAM04N cover, deep

FRAME H3Z RAM06N cover, standard

GRATE SET (H3 ROST 01)

REMOVABLE HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 180 mm

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!