

HEAT fireplace inserts WITH LIFTING STRAIGHT DOOR

HEAT fireplace inserts with lifting door are characterised by a simple, yet timeless design that will entice even the most discerning customers. The clean and minimalistic lines respond to the requirements of today's residential architecture.

HEAT fireplace inserts have large-format printed glazing that allows you to experience the fire in a unique way. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The combustion chamber is lined with heat-resistant bricks named IGNITON and is designed with no furnace grate. However the insert can be fitted with a grate at the customer's request. HEAT fireplace inserts are intended for convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. An EAI (external air intake) system is included. Tertiary air is brought into the combustion chamber to maximize combustion efficiency. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

HEAT 3G L 88.50.04



Prices on request at your seller

order code: **H3LF 04**

maximum of 2 side accumulation sets



Technical parameters

Height	1336 mm
Width	1184 mm
Depth	548 mm
Door height	466 mm
Door width	851 mm
Weight	272 kg
Regulated output	4,5-11,7 kW
Smoke flue diameter	150-200 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Draught	12 Pa
Efficiency	81,4 %
Average wood consumption	2,7 kg/h
A+	

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

CONVECTION COVER (H2LF KON01)

FRAME H3LF RAM11 cover standard

FRAME H3LF RAM12 cover standard

FRAME H3LF RAM13 standard

FRAME H3LF RAM14 standard

FRAME H3LF RAM15 support

GRATE SET (H3 ROST 04)

HANDLING SET

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)