

HEAT fireplace inserts WITH SIDE OPENING AND SPLIT CORNER GLAZING

HEAT corner fireplace inserts with side opening are a compelling and modern addition to any interior. Let their pleasant warmth captivate you - making any home cozier, adding a touch of timeless design and a unique atmosphere.

HEAT fireplace inserts are intended for convection as well as accumulation operation with the use of ventilation grates. Corner glazing (left, right) is made of two parts. The door frame is made of a special rigid rolled profile. The glass in the doors includes a design print. An EAI (external air intake) system is included. The combustion chamber is lined with chamotte bricks and a hinged iron grate with an ash tray. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. A MAMMOTH side accumulation set and upper accumulation rings can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert.

HEAT R/L 2G S 81.51.40.21



Prices on request at your seller

Split glazing - right variant - order code: HR2SF 21

Split glazing - left variant - order code: HL2SF 21

without grate set (optional)

maximum of 2 side accumulation sets









Technical parameters

 Height
 1146 mm

 Width
 874,5 mm

 Depth
 468,5 mm

 Door height
 470 mm

 Door width
 810 mm

 Door depth
 400 mm

 Weight
 186 kg

 Regulated output
 6.0-15.6 kg

Regulated output 6,0-15,6 kW

Smoke flue diameter 200 mm

Flue socket diameter 200 mm

External air intake diameter 150 mm

Draught 12 Pa

Efficiency 83,2 %

Average wood consumption 3,4 kg/h

A+

Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 02

FRAME HR2SF RAM06 4S universal, shallow

GRATE SET (H3 ROST 01)

REMOVABLE HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

Download

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!