

## IMPRESSION fireplace inserts WITH THREE-SIDED LIFTING DOOR AND SPLIT GLAZING

Our engineers designed the absolute jewel of the IMPRESSION collection. The fireplace insert with an unusually high three-sided glazing is able to transmit maximum heat to the living space lighting up the whole interior with flashes of fire. Do you like tuning the interior to the smallest detail? Choose the fireclay color - crema or black. The use of innovative design and cutting-edge materials is a matter of course.

IMPRESSION fireplace inserts have unusually high, printed three-sided glazing that allows you to experience the fire in a unique way. The easy, silent and precise operation of the lifting door is guaranteed by the state-of-the-art SILENT LIFT system. The lifting door is operated using a removable handle, which can optionally be replaced by a fixed handle. The combustion chamber is available in black or cream colour with an optional change for the furnace grate. Inserts are designed for both accumulation and convection operation. The innovative DOUBLE SPIN flue gas system increases efficiency and reduces the environmental impact of the fireplace insert. Secondary air intake washes over the glass in the door to prevent the cumulation of deposits. Primary and secondary air intake is regulated by a single control element. Fireplace inserts are equipped with a EAI (external air intake), which can be easily connected using the AIRBOX rotating elbow. Side and top MAMMOTH accumulation sets can be purchased separately for fireplace inserts, which can extend the period of heat radiation by more than 12 hours.

### IMPRESSION C 2G L 80.61.34.21



Prices on request at your seller

order code: **IC2LG 21**

maximum of 1 side accumulation set

the combustion chamber is optional (crema or black) and needs be ordered separately!



## Technical parameters

Height	1625 mm
Width	916 mm
Depth	610 mm
Door height	556 mm
Door width	800 mm
Door depth	340 mm
Weight*	248 kg
Regulated output	6,3-16,4 kW
Smoke flue diameter	180-200 mm
Flue socket diameter	200 mm
External air intake diameter	150 mm
Axis height of rear outlet	1168 mm
Draught	12 Pa
Efficiency	84,4 %
Average wood consumption	3,5 kg/h

\*weight including black / cream combustion chamber

A+

## Accessories

ADJUSTABLE LEGS - 190 mm

AIRBOX 01 IMPRESSION

COMBUSTION CHAMBER IC2LG TOP01 black

COMBUSTION CHAMBER IC2LG TOP02 cream

CONVECTION COVER for IMPRESSION C 2G L 80.61.34.21 fireplace insert

FRAME IC2LG RAM11 cover standard

FRAME IC2LG RAM12 cover standard

FRAME IC2LG RAM13 standard

FRAME IC2LG RAM14 standard

FRAME IC2LG RAM15 support

GRATE SET (H3 ROST 01)

HANDLING SET

IMPRESSION FIXED HANDLE

SIDE ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts

TOP ROMOTOP MAMMOTH ACCUMULATION SET for fireplace inserts with a flue exhaust of 200 mm

## **Download**

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)