

The ALEA fireplace stove includes a rotating design that allows you to enjoy viewing the flames from multiple angles.

ALEA A Fireplace stoves

The ALEA A fireplace stove will always adapt to your needs. Its rotating combustion chamber ensures you will always have a great view of the beautiful dancing flames, and the accumulation system above the combustion chamber will let you make great use of the heat released during combustion.

This fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. Additionally, you can purchase extra accumulation elements that radiate heat for up to 4 hours. The rotating combustion chamber allows you to view your fire from multiple angles.

ALEA 02 A

serpentine



Prices on request at your seller

order code: **ALEA 02 A**

Technical parameters

Height	1584 mm
Width	468 mm
Depth	468 mm
Weight	178 kg
Regulated output	2,9-7,4 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	1129.5/1376.5 mm
Draught	12 Pa
Efficiency	82,9 %
Average wood consumption	1,6 kg/h
A+	

Accessories

Accumulation set for fireplace stoves (AKKUM 02)

Download

[Declaration about qualities](#)
[EC declaration of conformity](#)
[Ecodesign \(EU 2015/1185\)](#)
[Energy label and product sheet](#)
[Energy label \(EU 2015/1186\)](#)
[General instructions](#)
[Installation instructions](#)
[Technical documentation](#)
[Technical sheet](#)
[Warranty sheet](#)
[Download our catalogue!](#)