

The oval shape of the LUGANO fireplace stove lends your interior a cosy feeling. The design is accentuated by a fully glazed stove door.

LUGANO Fireplace stoves

Pleasant details such as a sill above the combustion chamber and a door handle give the LUGANO fireplace stove an elegant look.

This fireplace stove is suitable for low-energy homes. The stove door includes a large glazed area with a designer print. The ventilated designer handle permits use when the stove is lit. The door can be locked in the open position. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for a small amount of wood or tools.

LUGANO 02

serpentine



Prices on request at your seller

order code: **LUGANO 02**

Technical parameters

| | |
|------------------------------|------------|
| Height | 1224 mm |
| Width | 550 mm |
| Depth | 438 mm |
| Weight | 185 kg |
| Regulated output | 3,0-7,8 kW |
| Smoke flue diameter | 150 mm |
| Flue socket diameter | 150 mm |
| External air intake diameter | 125 mm |
| Axis height of rear outlet | 922 mm |
| Draught | 12 Pa |
| Efficiency | 81,9 % |
| Average wood consumption | 1,7 kg/h |
| A+ | |

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)