

The rotating mechanism of the STROMBOLI T and STROMBOLI G T fireplace stoves allows you to adjust the view of the fire at any time according to your wishes.

### **STROMBOLI T Fireplace stoves**

The STROMBOLI T stove combines the innovative technology and ecological principles of the NAVIA model with a unique rotating mechanism. This stove is built on a stable leg that allows you to rotate the entire body to enjoy the view of the flames from anywhere in your interior. STROMBOLI T has a modern combustion chamber that ensures efficient and clean combustion with minimal environmental impact, thanks to compliance with the latest emission standards. With the ability to insert wood up to 50 cm in length and a three-point door locking mechanism, this stove offers ease of use and increased safety. The range of various claddings as serpentine stone, ceramic tile or black-coated sheet metal allows you to tailor the look of the stove to your favourite style, with each option enhancing the elegant rounded shapes of the stove. Enjoy not only the warmth, but also the design that brings comfort and joy to any home.

An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element.

#### **STROMBOLI T**

ceramic



Prices on request at your seller

order code: STRYET 10



#### **Glaze colours**



# **Technical parameters**

Width 787 mm  Depth 374 mm  Weight 170 kg  Regulated output 3,6-9,2 kW  Smoke flue diameter 150 mm  Flue socket diameter 150 mm  External air intake diameter 125 mm  Axis height of rear outlet 854 mm  Draught 12 Pa  Efficiency 81,7 %	Height	996 mm
Weight 170 kg Regulated output 3,6-9,2 kW Smoke flue diameter 150 mm Flue socket diameter 150 mm External air intake diameter 125 mm Axis height of rear outlet 854 mm Draught 12 Pa	Width	787 mm
Regulated output 3,6-9,2 kW  Smoke flue diameter 150 mm  Flue socket diameter 150 mm  External air intake diameter 125 mm  Axis height of rear outlet 854 mm  Draught 12 Pa	Depth	374 mm
Smoke flue diameter 150 mm  Flue socket diameter 150 mm  External air intake diameter 125 mm  Axis height of rear outlet 854 mm  Draught 12 Pa	Weight	170 kg
Flue socket diameter 150 mm  External air intake diameter 125 mm  Axis height of rear outlet 854 mm  Draught 12 Pa	Regulated output	3,6-9,2 kW
External air intake diameter 125 mm  Axis height of rear outlet 854 mm  Draught 12 Pa	Smoke flue diameter	150 mm
Axis height of rear outlet 854 mm  Draught 12 Pa	Flue socket diameter	150 mm
Draught 12 Pa	External air intake diameter	125 mm
	Axis height of rear outlet	854 mm
Efficiency 81,7 %	Draught	12 Pa
	Efficiency	81,7 %
Average wood consumption 2,0 kg/h	Average wood consumption	2,0 kg/h

## **Download**

Α+

Declaration about qualities

EC declaration of conformity

Ecodesign (EU 2015/1185)

Energy label and product sheet

Energy label (EU 2015/1186)

General instructions

Installation instructions

Technical documentation

Technical sheet

Warranty sheet

Download our catalogue!