

TEON Fireplace stoves

The design of the TEON stove is straight and clearly defined by rectangular elements. In combination with its compact proportions, the stove will find its place in any modern interior.

The stove is equipped with a self-locking mechanism of open door, which makes it easy to operate and reload. You can rely on the two-point closing mechanism with fixed fixation to the body. The solid wood door handle perfectly complements the overall design of the stove. The customer can choose from two standard flue outlets - top or rear. The glass of the door on the inside washes the secondary air flowing in, which prevents the build-up of dirt. The stove has a EAI system - external air inlet so they are also suitable for low-energy houses.

TEON P

steel



Prices on request at your seller

order code: **TEOYDP 30**



Technical parameters

Height	1058 mm
Width	900 mm
Depth	380 mm
Weight	131 kg
Regulated output	2,9-7,5 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	947 mm
Draught	12 Pa
Efficiency	80,6 %
Average wood consumption	1,6 kg/h

A

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)