

Modern stoves with high efficiency. Whether you choose the classic ALEDO model or the ALEDO G with its elegant printed glass, both offer highly efficient combustion and are designed for maximum aesthetic appeal.

ALEDO G Fireplace stoves

ALEDO G fireplace stove enriches the traditional features of the ALEDO model with printed glass doors, which adds to its elegance. This design element emphasises the clean lines and modern aesthetics of the stove, while retaining all the functional advantages of its predecessor. ALEDO G is ideal for those looking for a technologically advanced solution with an extra touch of style. The large glass not only provides a breathtaking view of the fire, but also ensures that the heat is efficiently distributed into the space. The availability of variants with different types of cladding - such as serpentine stone, ceramic tiles or black sheet metal - allows users to create a harmonious addition to their home. At the heart of the model is a highly efficient combustion system that guarantees optimum performance and minimises fuel consumption. The stove meets the strictest environmental standards, which guarantees low emissions and makes it environmentally friendly. This combination of high efficiency and aesthetic flexibility makes the ALEDO stove the ideal choice for modern households looking for an economical yet aesthetically appealing heating solution.

This fireplace stove is suitable for low-energy homes. The stove includes an EAI (External Air Intake) system. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The bottom part of the stove can be used for storing a small amount of wood.

ALEDO G

ceramic



Prices on request at your seller

Design glazing - order code: **ALEXE 10**

Glaze colours



Technical parameters

Height	915 mm
Width	740 mm
Depth	371 mm
Weight	178 kg
Regulated output	3,4-8,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	787 mm
Draught	12 Pa
Efficiency	80,7 %
Average wood consumption	2,0 kg/h
A+	

Download

- [Declaration about qualities](#)
- [EC declaration of conformity](#)
- [Ecodesign \(EU 2015/1185\)](#)
- [Energy label and product sheet](#)
- [Energy label \(EU 2015/1186\)](#)
- [General instructions](#)
- [Installation instructions](#)
- [Technical documentation](#)
- [Technical sheet](#)
- [Warranty sheet](#)
- [Download our catalogue!](#)