

The fireplace stoves of the SEIDO 3S family bring an extraordinary aesthetic element to the home, which is emphasised by the name 3S - the symbol for the view of the flames from three sides. The panoramic front glass of each stove model is complemented by two side glass panes that give the stove a very special look.

SEIDO H 3S Fireplace stoves

The SEIDO H 3S model extends the basic version with the option of storage stones in the upper part of the stove, where they retain heat even after the fire is extinguished, which ensures better thermal comfort and overall heating efficiency. Ideal for low-energy spaces where a gradual release of heat energy is appropriate. In addition, high quality materials and advanced technology ensure long durability with minimal maintenance. The stove is available with elegant cladding to give any space an original look. For cladding, you can choose from the elegant Serpentine stone with its original pattern, those looking to match the interior will choose ceramic tiles or black metal cladding for more modern spaces.

The SEIDO H 3S fireplace stove is suitable for low-energy homes. An EAI (External Air Intake) system is included. The standard version includes the option to connect an upper or rear flue gas exhaust. Thanks to the secondary air intake, the door glass is air-washed to prevent the cumulation of soot. The combustion chamber is lined with chamotte brick tiles. The primary and secondary air intakes are regulated by a single control element. The lower part of the stove includes a storage area with a door for storing a small amount of wood or tools. The unit can be fitted with heat accumulation fittings, thus extending the time of heat radiation after the flame has extinguished.

SEIDO H 3S

steel



Prices on request at your seller

order code: **SEIYEHG 30**

Technical parameters

Height	1383 mm
Width	471 mm
Depth	431 mm
Weight	137 kg
Regulated output	3,0-7,8 kW
Smoke flue diameter	150 mm
Flue socket diameter	150 mm
External air intake diameter	125 mm
Axis height of rear outlet	921/1194 mm
Draught	12 Pa
Efficiency	78,7 %
Average wood consumption	1,8 kg/h

A

Accessories

Accumulation set for fireplace stoves (AKKUM 01)

Download

[Declaration about qualities](#)

[EC declaration of conformity](#)

[Ecodesign \(EU 2015/1185\)](#)

[Energy label and product sheet](#)

[Energy label \(EU 2015/1186\)](#)

[General instructions](#)

[Installation instructions](#)

[Technical documentation](#)

[Technical sheet](#)

[Warranty sheet](#)

[Download our catalogue!](#)